

<b>Model</b>	<b>B 3055 4WD</b>	<b>B 3065 4WD</b>	<b>B 3080 4WD</b>
<b>Engine</b>	<b>Perkins</b>	<b>Perkins</b>	<b>Perkins</b>
Emission level	Stage 3A	Stage 3A	Stage 3A
Engine serial code	1103D-33TA	1103D-33TA	1103D-33TA
Rated engine power [kW/hp/rpm] [ISO14396]	44/60/2200	50/68/2200	55,9/76/2200
Max. torque [Nm/rpm]	251/1400	280/1400	310/1400
Capacity [cm³] / no of cylinders	3300/3	3300/3	3300/3
Cylinder diameter x stroke [mm]	105/127	105/127	105/127
Type of air filter	Dry type, with warning indicator	Dry type, with warning indicator	Dry type, with warning indicator
Aspiration	Turbo&Intercooler	Turbo&Intercooler	Turbo&Intercooler
Fuel tank [lt]	74	74	74
<b>Transmission</b>			
Type of gearbox	12F+12R synchro shuttle transmission	12F+12R synchro shuttle transmission	12F+12R synchro shuttle transmission
Gearbox clutch	Dry type double disc clutch	Dry type double disc clutch	Dry type double disc clutch
Speeds [km/h-rpm]	34-2200	34-2200	34-2200
<b>Differential Lock &amp; Powered Front Axle</b>			
Differential lock engagement	Mechanical	Electro-hydraulic	Electro-hydraulic
4WD engagement	Mechanical	Electro-hydraulic	Electro-hydraulic
<b>PTO</b>			
PTO Type	Independent	Independent	Independent
PTO rpm - engine rpm	540-1890 / 540E-1594	540-1890 / 540E-1594	540-1890 / 540E-1594
<b>Brake</b>			
Brake	Hydraulically operated multi disc brakes	Hydraulically operated multi disc brakes	Hydraulically operated multi disc brakes
Parking brake	Mechanical with hand lever operated	Mechanical with hand lever operated	Mechanical with hand lever operated
Activate of 4WD by brake	Standard	Standard	Standard
<b>Auxiliary Hydraulics &amp; Rear Hydraulic Lift</b>			
Max. pump capacity, pump pressure [(lt/min)/bar]	45/195	45/195	45/195
Functions	Position, draft control, Auto-Lift	Position, draft control, Auto-Lift	Position, draft control, Auto-Lift
Auxiliary hydraulic [output/valves]	4/2	4/2	4/2
Max. lifting force [kg]	2200	3000	3000
<b>Dimensions and Weights</b>			
Weight [without ballast weights] [kg]	2780	2780	2820
Front ballast weight [kg]	6x22	8x22	8x22
Rear ballast weight [kg]	2x45/2x30	2x45/4x30	2x45/4x30
Total length, with front weights [mm]	4050	4050	4050
Wheelbase [mm]	2030	2030	2030
Front wheel track settings [mm]	1340-1488	1340-1488	1340-1488
Rear wheel track settings [mm]	1209-1344	1209-1344	1209-1344
Overall width [mm]	1622-1770	1622-1770	1622-1770
Overall height [mm]	2430	2430	2430
Ground clearance [mm]	280	280	280
<b>Tires</b>			
Option 1 [front]	280/70R16	280/70R16	280/70R16
Option 1 [rear]	380/70R24	380/70R24	380/70R24
Option 2 [front]	280/70R18	280/70R18	280/70R18
Option 2 [rear]	380/85R24	380/85R24	380/85R24
Option 3 [front]	280/70R18	280/70R18	280/70R18
Option 3 [rear]	340/85R28	340/85R28	340/85R28

Hattat Traktör Sanayi ve Ticaret A.Ş. has the right to change the designs and technical information specified in this brochure.